

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2021

Reviewed on 10/06/2021

1 Identification

- **Product identifier**
- **Trade name:** Ultimate Top Coat
- **Application of the substance / the mixture** Stone & Concrete Counter tops (Self-leveling).
- **Uses advised against**
Processes involving extreme heat use advised against.
Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).
Any use involving aerosol formation or vapour or dust release in excess of the assigned workplace exposure limits where workers are exposed without suitable respiratory protective equipment (RPE).
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Coval Group LLC
12811 Royal Drive. Suite 110
Stafford, TX 77477
email contact: sales@coval-group.com
- **Information department:** Product safety department.
- **Emergency telephone number:**
The American Association of Poison Control Centers (24-hour hotline): 1-800-222-1222

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Danger
- **Hazard-determining components of labeling:**
Isopropanol
methyl acetate
- **Hazard statements**
Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause drowsiness or dizziness.
- **Precautionary statements**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not breathe mist/vapours/spray.
Wear protective gloves/protective clothing/eye protection/face protection.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
In case of fire: Use CO2, powder or water spray to extinguish.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2021

Reviewed on 10/06/2021

Trade name: Ultimate Top Coat

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

67-63-0	Isopropanol	>20-≤40%
79-20-9	methyl acetate	>25-≤40%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
DO NOT DELAY!
Check for and remove any contact lenses.
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
DO NOT DELAY!
Wash mouth out with water
Do not induce vomiting; immediately call for medical help.
If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
- **Information for doctor:** Treat symptomatically and supportively.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2021

Reviewed on 10/06/2021

Trade name: Ultimate Top Coat

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Wear fully protective suit.
 - Do not inhale explosion gases or combustion gases.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Mount respiratory protective device.
 - Wear protective equipment. Keep unprotected persons away.
 - Ensure adequate ventilation
 - Particular danger of slipping on leaked/spilled product.
 - Keep ignition sources away - no smoking.
- **Environmental precautions:**
 - Do not allow to enter sewers/ surface or ground water.
 - Do not allow to penetrate the ground/soil.
- **Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Send for recovery or disposal in suitable receptacles.
 - Ensure adequate ventilation.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

79-20-9	methyl acetate	250 ppm
67-63-0	Isopropanol	400ppm

- **PAC-2:**

79-20-9	methyl acetate	1,700 ppm
67-63-0	Isopropanol	2,000 ppm

- **PAC-3:**

79-20-9	methyl acetate	10000* ppm
67-63-0	Isopropanol	12,000 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
 - Keep away from heat and direct sunlight.
 - Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.
 - Welding and other hot work operations in the work area must only be permitted under supervision.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2021

Reviewed on 10/06/2021

Trade name: Ultimate Top Coat

(Contd. of page 3)

- Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.
 - Store in a bunded area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

67-63-0 Isopropanol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

79-20-9 methyl acetate

PEL	Long-term value: 610 mg/m ³ , 200 ppm
REL	Short-term value: 760 mg/m ³ , 250 ppm Long-term value: 610 mg/m ³ , 200 ppm
TLV	Short-term value: 757 mg/m ³ , 250 ppm Long-term value: 606 mg/m ³ , 200 ppm

- **Ingredients with biological limit values:**

67-63-0 Isopropanol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

Select PPE appropriate for the operations taking place taking into account the product properties.

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid close or long term contact with the skin.
Do not inhale gases / fumes / aerosols.
Do not eat or drink while working.
Take note of assigned Workplace Exposure Limits.

- **Breathing equipment:**

Use suitable respiratory protective device in case of insufficient ventilation.
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
If respiratory protection is required, institute a complete respiratory protection program including selection, fit testing, training, maintenance and inspection.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2021

Reviewed on 10/06/2021

Trade name: Ultimate Top Coat

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection:

Solvent resistant protective clothing

Body protection must be chosen depending on product properties, activity and possible exposure.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Color: Clear

· **Odor:** Solvent like

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

· **Flash point:** -10 °C (14 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** >250 °C (>482 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 2 Vol %

Upper: 16 Vol %

· **Vapor pressure:** Not determined.

· **Density:** Not determined.

· **Relative density:** Not determined.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2021

Reviewed on 10/06/2021

Trade name: Ultimate Top Coat

(Contd. of page 5)

· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	NOTE: The physical data presented above are typical values and should not be construed as a specification.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Strong oxidising agents.
- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Metal oxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:**
Will defat and dry the skin.
Frequent or prolonged contact may irritate and cause dermatitis.
- **on the eye:** Irritating effect.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** The organic portion of the product is biodegradable.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2021

Reviewed on 10/06/2021

Trade name: Ultimate Top Coat


(Contd. of page 6)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** Product is not expected to bioaccumulate.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Recommended Hierarchy of Controls:
 - Minimise waste;
 - Reuse if not contaminated;
 - Recycle, if possible; or
 - Safe disposal (if all else fails).
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Contact waste processors for recycling information.
Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.
- **Uncleaned packagings:**
- **Recommendation:**
Disposal must be made according to official regulations.
Container remains hazardous when empty. Continue to observe all precautions.
Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.
Do not mix with other waste streams.

14 Transport information

- | | |
|---|---|
| · UN-Number | UN1139 |
| · DOT, ADR, IMDG, IATA | |
| · UN proper shipping name | Coating solution |
| · DOT | 1139 COATING SOLUTION, special provision 640D |
| · ADR | COATING SOLUTION |
| · IMDG, IATA | |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |

(Contd. on page 8)

US

Safety Data Sheet


acc. to OSHA HCS

Printing date 10/06/2021

Reviewed on 10/06/2021

Trade name: Ultimate Top Coat

(Contd. of page 7)

· Label	3
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
Not applicable.	
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1139 COATING SOLUTION, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- TSCA (Toxic Substances Control Act): All ingredients are listed.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2021

Reviewed on 10/06/2021

Trade name: Ultimate Top Coat

(Contd. of page 8)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms GHS02, GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Isopropanol

methyl acetate

· Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

In case of fire: Use CO₂, powder or water spray to extinguish.
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact:
· Date of preparation / last revision 10/06/2021 / -

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3