

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Revision: 16.10.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· **Trade name:** Anti-Graffiti Coat

· **Registration number** Mixture

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Application of the substance / the mixture** Surface treatment product

· **Uses advised against**

Processes involving extreme heat use advised against.

Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).

Any use involving aerosol formation or vapour or dust release in excess of the assigned workplace exposure limits where workers are exposed without suitable respiratory protective equipment (RPE).

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Coval Group LLC

12811 Royal Dr. 110

Stafford, TX 77477

email: contact@coval-group.com

· **Further information obtainable from:** Product safety department.

· **1.4 Emergency telephone number:**

UK National Poisons Information Service. E-mail: npis.birmingham@nhs.net; Tel: +44 (0)344 892 0111

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms** GHS02, GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

methyl acetate

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe mist/vapors/spray.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Revision: 16.10.2021

Trade name: Anti-Graffiti Coat

(Contd. of page 1)

- P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 79-20-9	methyl acetate	>25-≤100%
EINECS: 201-185-2	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
DO NOT DELAY!
Check for and remove any contact lenses.
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
DO NOT DELAY!
Wash mouth out with water
Do not induce vomiting; call for medical help immediately.
If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
- **Information for doctor:** Treat symptomatically and supportively.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Revision: 16.10.2021

Trade name: Anti-Graffiti Coat

(Contd. of page 2)

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

- Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation
- Particular danger of slipping on leaked/spilled product.
- Keep ignition sources away - no smoking.

· **6.2 Environmental precautions:**

- Do not allow to enter sewers/ surface or ground water.
- Do not allow to penetrate the ground/soil.

· **6.3 Methods and material for containment and cleaning up:**

- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Send for recovery or disposal in suitable receptacles.
- Ensure adequate ventilation.

· **6.4 Reference to other sections**

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Keep away from heat and direct sunlight.
- Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.
- Welding and other hot work operations in the work area must only be permitted under supervision.

· **Information about fire - and explosion protection:**

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

- Store in a cool location.
- Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- Store in a bunded area.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

-GB-

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Revision: 16.10.2021

Trade name: Anti-Graffiti Coat

(Contd. of page 3)

· Ingredients with limit values that require monitoring at the workplace:
79-20-9 methyl acetate

WEL	Short-term value: 770 mg/m ³ , 250 ppm
	Long-term value: 616 mg/m ³ , 200 ppm

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid close or long term contact with the skin.
- Do not inhale gases / fumes / aerosols.
- Do not eat or drink while working.
- Take note of assigned Workplace Exposure Limits.

· **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:


Tightly sealed goggles

· Body protection:

Solvent resistant protective clothing
Body protection must be chosen depending on product properties, activity and possible exposure.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties
· General Information
· Appearance:

Form:	Fluid
Colour:	Clear
· Odour:	Solvent like
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Revision: 16.10.2021

Trade name: Anti-Graffiti Coat

(Contd. of page 4)

Initial boiling point and boiling range:	Undetermined.
· Flash point:	-10 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	>250 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not self-igniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
· Vapour pressure:	Not determined.
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	0.18 log POW
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· 9.2 Other information	NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Strong oxidising agents.
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Metal oxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Will defat and dry the skin.
Frequent or prolonged contact may irritate and cause dermatitis.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Revision: 16.10.2021

Trade name: Anti-Graffiti Coat

(Contd. of page 5)

- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** The organic portion of the product is biodegradable.
- **12.3 Bioaccumulative potential** Product is not expected to bioaccumulate.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Recommended Hierarchy of Controls:
 - Minimise waste;
 - Reuse if not contaminated;
 - Recycle, if possible; or
 - Safe disposal (if all else fails).
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Contact waste processors for recycling information.
Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Container remains hazardous when empty. Continue to observe all precautions.
Do not mix with other waste streams.
Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

SECTION 14: Transport information

- | | |
|---------------------------------------|---|
| · 14.1 UN-Number | |
| · ADR, IMDG, IATA | UN1139 |
| · 14.2 UN proper shipping name | |
| · ADR | 1139 COATING SOLUTION, special provision 640D |

(Contd. on page 7)

Safety data sheet


according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Revision: 16.10.2021

Trade name: Anti-Graffiti Coat

(Contd. of page 6)

· IMDG, IATA	COATING SOLUTION
· 14.3 Transport hazard class(es) · ADR, IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S</u> -E B
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1139 COATING SOLUTION, SPECIAL PROVISION 640D, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **National regulations:**
- **Information about limitation of use:**

Class	Share in %
NK	70.0

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Revision: 16.10.2021

Trade name: Anti-Graffiti Coat

(Contd. of page 7)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB