

Safety data sheet according to the globally harmonized system

Printing date 19.05.2023

Version number 2

Revision: 19.05.2023

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Concrete Primer
- **Registration number** Mixture
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Application of the substance / the mixture**
Protective coating
Sealant
- **Uses advised against**
Processes involving extreme heat use advised against.
Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).
Any use involving aerosol formation or vapour release in excess of the assigned WEL where workers are exposed without suitable RPE.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Coval Technologies
12811 Royal Drive, Suite 110
Stafford, TX 77477
USA
Tel: +1 281 566 4277
email: rcrowe@covaltechnologies.com
- **Further information obtainable from:** Product safety department.
- **Emergency telephone number:** Kuwait Ministry of Health hotline - Tel: 151

2 Hazards identification

- **Classification of the substance or mixture**



flame

Flam. Liq. 2

H225 Highly flammable liquid and vapour.



Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

Acute Tox. 5

H303 May be harmful if swallowed.

- **Label elements**
- **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Danger
- **Hazard statements**
Highly flammable liquid and vapour.
May be harmful if swallowed.

(Contd. on page 2)

KW

Safety data sheet according to the globally harmonized system

Printing date 19.05.2023

Version number 2

Revision: 19.05.2023

Trade name: Concrete Primer

(Contd. of page 1)

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep out of reach of children.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not breathe mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterisation: Mixtures**

· **Description:** A solution of polymers in solvent with multifunctional additives.

· **Dangerous components:**

79-20-9	methyl acetate	50–100%
	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336; Acute Tox. 5, H303	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Do not induce vomiting; call for medical help immediately.

If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

· **Information for doctor:** Treat symptomatically and supportively.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

—KW—

(Contd. on page 3)



Safety data sheet according to the globally harmonized system

Printing date 19.05.2023

Version number 2

Revision: 19.05.2023

Trade name: Concrete Primer

(Contd. of page 2)

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
Flammable. Vapors may travel to source of ignition and flash back.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
Do not inhale explosion gases or combustion gases.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Particular danger of slipping on leaked/spilled product.
Keep ignition sources away - no smoking.
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow to penetrate the ground/soil.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Send for recovery or disposal in suitable receptacles.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep away from heat and direct sunlight.
Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.
Welding and other hot work operations in the work area must only be permitted under supervision.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.

(Contd. on page 4)

KW

Safety data sheet
according to the globally harmonized system

Printing date 19.05.2023

Version number 2

Revision: 19.05.2023

Trade name: Concrete Primer

(Contd. of page 3)

- Protect against electrostatic charges.
- Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Prevent any seepage into the ground.
Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Protect from heat and direct sunlight.
Store in a banded area.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

79-20-9 methyl acetate

PEL (USA)	Long-term value: 610 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 760 mg/m ³ , 250 ppm Long-term value: 610 mg/m ³ , 200 ppm
TLV (USA)	Short-term value: 250 ppm Long-term value: 200 ppm
WEL (Great Britain)	Short-term value: 770 mg/m ³ , 250 ppm Long-term value: 616 mg/m ³ , 200 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Do not eat or drink while working.
Take note of assigned Workplace Exposure Limits.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**



Protective gloves.
Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Safety data sheet according to the globally harmonized system

Printing date 19.05.2023

Version number 2

Revision: 19.05.2023

Trade name: Concrete Primer

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles conforming to EN166.

- **Body protection:**

Solvent resistant protective clothing

Body protection must be chosen depending on product properties, activity and possible exposure.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Colour:	Light brown
Odour:	Solvent like
Odour threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

- **Flash point:** -10 °C

- **Flammability (solid, gas):** Highly flammable.

- **Auto-ignition temperature:** > 250 °C

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not self-igniting.

- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower:	3.1 Vol %
Upper:	16 Vol %

- **Vapour pressure at 20 °C:** 220 hPa

- **Density at 20 °C:** 0.95 g/cm³

(Contd. on page 6)



Safety data sheet according to the globally harmonized system

Printing date 19.05.2023

Version number 2

Revision: 19.05.2023

Trade name: Concrete Primer

(Contd. of page 5)

· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	0.18 log POW
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic:	Not determined.
· Solvent content:	
· VOC (EC)	80.00 %
· Other information	NOTE: The physical data presented above are typical values and should not be construed as a specification.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Strong oxidising agents.
- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Metal oxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral | LD50 | 4,631 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Will defat and dry the skin.
Frequent or prolonged contact may irritate and cause dermatitis.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Subacute to chronic toxicity:**
Chronic effects:: Skin damage due to contact with the liquid; high exposures might entail damage of the optic nerve.

(Contd. on page 7)

KW



Safety data sheet according to the globally harmonized system

Printing date 19.05.2023

Version number 2

Revision: 19.05.2023

Trade name: Concrete Primer

(Contd. of page 6)

· Additional toxicological information:

Routes of exposure: The main route of exposure is via the respiratory tract.

EFFECTS OF SHORT-TERM EXPOSURE: The product is irritating to the eyes and the respiratory tract. May cause effects on the central nervous system.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicity

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** The organic portion of the product is biodegradable.

· Behaviour in environmental systems:

· **Bioaccumulative potential** Product is not expected to bioaccumulate.

· **Mobility in soil** No further relevant information available.

· Additional ecological information:**· General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods**· Recommendation**

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

· Uncleaned packaging:**· Recommendation:**

Container remains hazardous when empty. Continue to observe all precautions.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

KW

(Contd. on page 8)

Safety data sheet
according to the globally harmonized system

Printing date 19.05.2023


Version number 2

Revision: 19.05.2023

Trade name: Concrete Primer

(Contd. of page 7)

14 Transport information

· UN-Number · ADR, IMDG, IATA	UN1139
· UN proper shipping name · ADR · IMDG, IATA	UN1139 COATING SOLUTION, special provision 640D COATING SOLUTION
· Transport hazard class(es) · ADR, IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· Packing group · ADR, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S</u> -E B
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1139 COATING SOLUTION, 3, II

KW

(Contd. on page 9)

Safety data sheet according to the globally harmonized system

Printing date 19.05.2023

Version number 2

Revision: 19.05.2023

Trade name: Concrete Primer

(Contd. of page 8)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture**· GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms GHS02, GHS07**· Signal word** Danger**· Hazard statements**

Highly flammable liquid and vapour.

May be harmful if swallowed.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep out of reach of children.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not breathe mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

· Directive 2012/18/EU**· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category** P5c**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**· National regulations:****· Information about limitation of use:**

Class	Share in %
NK	80.0

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H303 May be harmful if swallowed.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Contact:**· Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 10)



Safety data sheet
according to the globally harmonized system

Printing date 19.05.2023

Version number 2

Revision: 19.05.2023

Trade name: Concrete Primer

(Contd. of page 9)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 5: Acute toxicity – Category 5
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

-KW-