

## Safety data sheet according SS 586 : Part 3

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

### 1 Identification

**· Product identifier****· Trade name:** Concrete Coat**· Registration number** Mixture**· Relevant identified uses of the substance or mixture and uses advised against****· Product category** PC9a Coatings and paints, thinners, paint removers**· Application of the substance / the mixture** Coating**· Uses advised against**

Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).

Any use involving significant release of aerosol, vapour or dust in the breathing zone of workers where they are exposed without suitable respiratory protective equipment (RPE).

Processes involving the use of incompatible substances - refer to section 10.

Processes involving extreme heat use advised against.

**· Details of the supplier of the safety data sheet****· Manufacturer/Supplier:**

Coval Technologies

3 Fusionopolis Place

04-54 Galaxis Work Loft

Singapore 138523

Phone: +65 6568 3903

**· Further information obtainable from:** Product safety department.**· Emergency telephone number:** +65 6568 3903

### 2 Hazards identification

**· Classification of the substance or mixture**

Flam. Liq. 2

H225 Highly flammable liquid and vapour.



Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

**· Label elements****· GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

**· Hazard pictograms** GHS02, GHS07**· Signal word** Danger**· Hazard-determining components of labelling:**

methyl acetate

**· Hazard statements**

Highly flammable liquid and vapour.

Causes serious eye irritation.

(Contd. on page 2)

SG

# Safety data sheet

## according SS 586 : Part 3

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

**Trade name: Concrete Coat**

(Contd. of page 1)

May cause drowsiness or dizziness.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

79-20-9	methyl acetate	☠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	30-70%
67-63-0	Isopropanol	☠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

- **Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

- **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- **After eye contact:**

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Do not induce vomiting; call for medical help immediately.

If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

- **Information for doctor:** Treat symptomatically and supportively.

- **Most important symptoms and effects, both acute and delayed**

Disorientation

Dizziness

Headache

Nausea

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 3)

# Safety data sheet

## according SS 586 : Part 3

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

**Trade name: Concrete Coat**

(Contd. of page 2)

- **Special hazards arising from the substance or mixture**  
Flammable. Vapors may travel to source of ignition and flash back.  
Vapours are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur.  
In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- **Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.  
Wear fully protective suit.
- **Additional information**  
Cool endangered receptacles with water spray.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Particular danger of slipping on leaked/spilled product.  
Keep ignition sources away - no smoking.  
Vapours are heavier than air. They can spread along the ground and collect in confined spaces.
- **Environmental precautions:**  
Do not allow to penetrate the ground/soil.  
Do not allow to enter sewers/ surface or ground water.  
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**  
Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Safety showers and eye wash facilities should be available at the work area.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed receptacles.  
Store receptacle in a well ventilated area.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

SG

(Contd. on page 4)

# Safety data sheet

## according SS 586 : Part 3

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 3)

### 8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see section 7.

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

#### 79-20-9 methyl acetate

PEL Short-term value: 757 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 606 mg/m<sup>3</sup>, 200 ppm

WSH Short-term value: 757 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 606 mg/m<sup>3</sup>, 200 ppm

#### 67-63-0 Isopropanol

PEL Short-term value: 1230 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 983 mg/m<sup>3</sup>, 400 ppm

WSH Short-term value: 1230 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 983 mg/m<sup>3</sup>, 400 ppm

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Ensure that eyewash stations and safety showers are close to the workstation location.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A for organic vapours

· **Protection of hands:**



Protective gloves.

Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses with side-shields conforming to EN166.

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Goggles recommended during refilling

(Contd. on page 5)

# Safety data sheet

## according SS 586 : Part 3

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 4)

· **Body protection:**

Protective work clothing

Body protection must be chosen depending on product properties, activity and possible exposure.

### 9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· <b>Form:</b>	Liquid
· <b>Colour:</b>	Colourless
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.· **Change in condition**

· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Initial boiling point and boiling range:</b>	>57 °C

· **Flash point:** -10 °C· **Flammability (solid, gas):** Highly flammable.· **Auto-ignition temperature:** 425 °C· **Decomposition temperature:** Not determined.· **Ignition temperature:** Product is not self-igniting.· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Explosion limits:**

· <b>Lower:</b>	3.1 Vol %
· <b>Upper:</b>	16 Vol %

· **Vapour pressure at 20 °C:** 220 hPa· **Vapour pressure at 50 °C:** 800 hPa· **Density at 20 °C:** 0.85 g/cm<sup>3</sup>· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with water:**

Fully miscible.

· **Partition coefficient: n-octanol/water:** Not determined.· **Viscosity:**· **Dynamic:** Not determined.· **Kinematic:** Not determined.· **Solvent content:**· **VOC (EC)** 59.00 %· **Other information**

No further relevant information available.

SG

(Contd. on page 6)

# Safety data sheet

## according SS 586 : Part 3

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 5)

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
At elevated temperatures, explosive vapour/air mixtures may be formed.  
Heating will cause rise in pressure of container with risk of bursting.
- **Possibility of hazardous reactions**  
Reacts with oxidising agents.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
- **Conditions to avoid** Heat and static discharge.
- **Incompatible materials:** Strong oxidising agents.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

#### ATE (Acute Toxicity Estimates)

Oral	LD50	>5,557 mg/kg
------	------	--------------

#### 79-20-9 methyl acetate

Oral	LD50	3,705 mg/kg (rabbit)
------	------	----------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**  
ROUTES OF EXPOSURE: Can be absorbed into the body by inhalation and by ingestion.  
INHALATION RISK: A harmful contamination of the air will be reached very quickly on evaporation of this substance at 20°C.  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

-SG-

(Contd. on page 7)

# Safety data sheet

## according SS 586 : Part 3

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 6)

### 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation**

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

- **Uncleaned packaging:**

- **Recommendation:**

Container remains hazardous when empty. Continue to observe all precautions.

Disposal must be made according to official regulations.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

Do not mix with other waste streams.

- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

### 14 Transport information

- **UN-Number**

· **ADR/RID/ADN, IMDG, IATA**

UN1139

- **UN proper shipping name**

· **ADR/RID/ADN**

UN1139 COATING SOLUTION, special provision 640D

· **IMDG, IATA**

COATING SOLUTION

- **Transport hazard class(es)**

· **ADR/RID/ADN, IMDG, IATA**· **Class**

3 Flammable liquids.

· **Label**

3

- **Packing group**

· **ADR/RID/ADN, IMDG, IATA**

II

- **Environmental hazards:**

Not applicable.

- **Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):**

33

· **EMS Number:**F-E,S-E· **Stowage Category**

B

- **Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

(Contd. on page 8)

# Safety data sheet

## according SS 586 : Part 3

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

**Trade name: Concrete Coat**

(Contd. of page 7)

**· Transport/Additional information:**
**· ADR/RID/ADN**
**· Limited quantities (LQ)**

5L

**· Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

**· Transport category**

2

**· Tunnel restriction code**

D/E

**· IMDG**
**· Limited quantities (LQ)**

5L

**· Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

**· UN "Model Regulation":**

UN 1139 COATING SOLUTION, 3, II

## 15 Regulatory information

**· Safety, health and environmental regulations/legislation specific for the substance or mixture**
**· Poisons Act - Schedule 1**

None of the ingredients is listed.

**· Poisons Act - Schedule 2, Group II**

None of the ingredients is listed.

**· Health Products Act - First Schedule - Psychotropic Substances**

None of the ingredients is listed.

**· GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

**· Hazard pictograms** GHS02, GHS07

**· Signal word** Danger

**· Hazard-determining components of labelling:**

methyl acetate

**· Hazard statements**

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

**· Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Directive 2012/18/EU**
**· Named dangerous substances - ANNEX I** None of the ingredients is listed.

**· Seveso category** P5c

**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

(Contd. on page 9)



# Safety data sheet

## according SS 586 : Part 3

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

**Trade name: Concrete Coat**

(Contd. of page 8)

· **National regulations:**

· **Information about limitation of use:**

Class	Share in %
NK	59.0

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Contact:**

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

SG