

Safety data sheet according to 1907/2006/EC, Article 31 as amended

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· **Trade name:** Concrete Coat

· **Registration number** Mixture

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Application of the substance / the mixture** Coating

· **Uses advised against**

Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).

Any use involving significant release of aerosol, vapour or dust in the breathing zone of workers where they are exposed without suitable respiratory protective equipment (RPE).

Processes involving the use of incompatible substances - refer to section 10.

Processes involving extreme heat use advised against.

· 1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

Coval Technologies

12811 Royal Drive, Suite 110

Stafford, TX 77477

USA

Tel: +1 281 566 4277

email: rcrowe@covaltechnologies.com

· **Further information obtainable from:** Product safety department.

· 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms** GHS02, GHS07

· **Signal word** Danger

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31 as amended

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 1)

· **Hazard-determining components of labelling:**

methyl acetate

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 79-20-9	methyl acetate	30-70%
EINECS: 201-185-2	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 67-63-0	Isopropanol	2.5-<10%
EINECS: 200-661-7	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31 as amended

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 2)

- **After swallowing:**
 - Wash mouth out with water
 - Do not induce vomiting; call for medical help immediately.
 - If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
- **Information for doctor:** Treat symptomatically and supportively.
- **4.2 Most important symptoms and effects, both acute and delayed**
 - Disorientation
 - Dizziness
 - Headache
 - Nausea
- **4.3 Indication of any immediate medical attention and special treatment needed**
 - No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
 - CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 - Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
 - Flammable. Vapors may travel to source of ignition and flash back.
 - Vapours are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur.
 - In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- **5.3 Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Do not inhale explosion gases or combustion gases.
 - Wear fully protective suit.
- **Additional information**
 - Cool endangered receptacles with water spray.
 - Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
 - Particular danger of slipping on leaked/spilled product.
 - Keep ignition sources away - no smoking.
 - Vapours are heavier than air. They can spread along the ground and collect in confined spaces.
- **6.2 Environmental precautions:**
 - Do not allow to penetrate the ground/soil.
 - Do not allow to enter sewers/ surface or ground water.
 - Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
 - Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31 as amended

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 3)

- Ensure adequate ventilation.
- **6.4 Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Safety showers and eye wash facilities should be available at the work area.
- **Information about fire - and explosion protection:**
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:**
- Store in cool, dry conditions in well sealed receptacles.
- Store receptacle in a well ventilated area.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**

79-20-9 methyl acetate

WEL	Short-term value: 770 mg/m ³ , 250 ppm
	Long-term value: 616 mg/m ³ , 200 ppm

67-63-0 Isopropanol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm
	Long-term value: 999 mg/m ³ , 400 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**
- **Personal protective equipment:**

· **General protective and hygienic measures:**

- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Do not eat, drink, smoke or sniff while working.
- Do not carry product impregnated cleaning cloths in trouser pockets.
- Wash hands before breaks and at the end of work.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31 as amended

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 4)

Avoid contact with the eyes and skin.
Ensure that eyewash stations and safety showers are close to the workstation location.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.
Filter A for organic vapours

· **Protection of hands:**



Protective gloves.

Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses with side-shields conforming to EN166.

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Goggles recommended during refilling

· **Body protection:**



Protective work clothing

Body protection must be chosen depending on product properties, activity and possible exposure.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	>57 °C

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31 as amended

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 5)

· Flash point:	-10 °C
· Flammability (solid, gas):	Highly flammable.
· Auto-ignition temperature:	425 °C
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not self-igniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
· Vapour pressure at 20 °C:	220 hPa
· Vapour pressure at 50 °C:	800 hPa
· Density at 20 °C:	0.85 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Fully miscible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC (EC)	59.00 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
At elevated temperatures, explosive vapour/air mixtures may be formed.
Heating will cause rise in pressure of container with risk of bursting.
- **10.3 Possibility of hazardous reactions**
Reacts with oxidising agents.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
- **10.4 Conditions to avoid** Heat and static discharge.
- **10.5 Incompatible materials:** Strong oxidising agents.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

GB

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31 as amended

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 6)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

79-20-9 methyl acetate

Oral	LD50	3,705 mg/kg (rabbit)
------	------	----------------------

· **Primary irritant effect:**

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.

· **Serious eye damage/irritation**

Causes serious eye irritation.

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

· **Additional toxicological information:**

ROUTES OF EXPOSURE: Can be absorbed into the body by inhalation and by ingestion.

INHALATION RISK: A harmful contamination of the air will be reached very quickly on evaporation of this substance at 20°C.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

- **Carcinogenicity** Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure**

May cause drowsiness or dizziness.

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- **Aquatic toxicity:** No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· **Recommendation**

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31 as amended

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 7)

- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

· **Uncleaned packaging:**

· **Recommendation:**

Container remains hazardous when empty. Continue to observe all precautions.

Disposal must be made according to official regulations.

Containers, even those that are “empty,” may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

Do not mix with other waste streams.

- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR/RID/ADN, IMDG, IATA** UN1139

· **14.2 UN proper shipping name**

· **ADR/RID/ADN** UN1139 COATING SOLUTION, special provision 640D
 · **IMDG, IATA** COATING SOLUTION

· **14.3 Transport hazard class(es)**

· **ADR/RID/ADN, IMDG, IATA**



· **Class** 3 Flammable liquids.

· **Label** 3

· **14.4 Packing group**

· **ADR/RID/ADN, IMDG, IATA** II

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):** 33

· **EMS Number:** F-E,S-E

· **Stowage Category** B

· **14.7 Transport in bulk according to Annex II of**

Marpol and the IBC Code Not applicable.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31 as amended

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

(Contd. of page 8)

· **Transport/Additional information:**

· **ADR/RID/ADN**

- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**

5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **Transport category**
- **Tunnel restriction code**

2
D/E

· **IMDG**

- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**

5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **UN "Model Regulation":**

UN 1139 COATING SOLUTION, 3, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **Information about limitation of use:**

Class	Share in %
NK	59.0

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances

(Contd. on page 10)



Safety data sheet
according to 1907/2006/EC, Article 31 as amended

Printing date 18.08.2023

Version number 1

Revision: 18.08.2023

Trade name: Concrete Coat

CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. of page 9)

GB