

Safety data sheet according SS 586 : Part 3

Printing date 16.08.2023

Version number 1

Revision: 10.07.2023

1 Identification

· **Product identifier**

· **Trade name:** Concrete Primer

· **Registration number** Mixture

· **Relevant identified uses of the substance or mixture and uses advised against**

· **Product category** PC15 Non-metal-surface treatment products

· **Application of the substance / the mixture** Primer/ Subcoating

· **Uses advised against**

Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).

Any use involving significant release of aerosol, vapour or dust in the breathing zone of workers where they are exposed without suitable respiratory protective equipment (RPE).

Processes involving extreme heat use advised against.

Processes involving the use of incompatible substances - refer to section 10.

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Coval Technologies

12811 Royal Drive, Suite 110

Stafford, TX 77477

USA

Tel: +1 281 566 4277

email: rcrowe@covaltechnologies.com

· **Further information obtainable from:** Product safety department.

· **Emergency telephone number:** +65 6568 3903

2 Hazards identification

· **Classification of the substance or mixture**



flame

Flam. Liq. 2

H225 Highly flammable liquid and vapour.



Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms** GHS02, GHS07

· **Signal word** Danger

· **Hazard statements**

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

(Contd. on page 2)

Safety data sheet according SS 586 : Part 3

Printing date 16.08.2023

Version number 1

Revision: 10.07.2023

Trade name: Concrete Primer



(Contd. of page 1)

- Use explosion-proof electrical/ventilating/lighting equipment.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

67-64-1	Acetone		50–100%
79-20-9	methyl acetate		10–<20%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
 Supply fresh air; consult doctor in case of complaints.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
 Immediately wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.
- **After eye contact:**
 Check for and remove any contact lenses.
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
 Do not induce vomiting; call for medical help immediately.
 If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
- **Information for doctor:** Treat symptomatically and supportively.
- **Most important symptoms and effects, both acute and delayed** Dizziness
- **Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 Use fire extinguishing methods suitable to surrounding conditions.

(Contd. on page 3)

Safety data sheet according SS 586 : Part 3

Printing date 16.08.2023

Version number 1

Revision: 10.07.2023

Trade name: Concrete Primer

(Contd. of page 2)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
Flammable. Vapors may travel to source of ignition and flash back.
In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow to penetrate the ground/soil.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Contain and collect spillage with non-combustible, absorbent material e.g.sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Do not use combustible materials such as paper towels to clean up spills.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Do not store on combustible materials such as wooden floors or wooden pallets.
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:**
Do not store together with oxidising and acidic materials.

(Contd. on page 4)

Safety data sheet according SS 586 : Part 3

Printing date 16.08.2023

Version number 1

Revision: 10.07.2023

Trade name: Concrete Primer

(Contd. of page 3)

- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 Acetone

PEL	Short-term value: 2380 mg/m ³ , 1000 ppm Long-term value: 1780 mg/m ³ , 750 ppm
WSH	Short-term value: 2380 mg/m ³ , 1000 ppm Long-term value: 1780 mg/m ³ , 750 ppm

79-20-9 methyl acetate

PEL	Short-term value: 757 mg/m ³ , 250 ppm Long-term value: 606 mg/m ³ , 200 ppm
WSH	Short-term value: 757 mg/m ³ , 250 ppm Long-term value: 606 mg/m ³ , 200 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Ensure that eyewash stations and safety showers are close to the workstation location.
Do not carry product impregnated cleaning cloths in trouser pockets.

- **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.
Filter A for organic vapours

- **Protection of hands:**



Protective gloves.

Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety data sheet according SS 586 : Part 3

Printing date 16.08.2023

Version number 1

Revision: 10.07.2023

Trade name: Concrete Primer

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:


Safety glasses with side-shields conforming to EN166.

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Goggles recommended during refilling

· Body protection:


Protective work clothing

Body protection must be chosen depending on product properties, activity and possible exposure.

9 Physical and chemical properties

· Information on basic physical and chemical properties
· General Information
· Appearance:

Form: Fluid
Colour: According to product specification

· Odour: Characteristic

· Odour threshold: Not determined.

· pH-value at 20 °C: 7

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 55.8–56.6 °C

· Flash point: -10 °C

· Flammability (solid, gas): Highly flammable.

· Auto-ignition temperature: 455 °C

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not self-igniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 2.6 Vol %

Upper: 16 Vol %

· Vapour pressure at 20 °C: 233 hPa

· Vapour pressure at 50 °C: 800 hPa

· Density at 20 °C: 0.85 g/cm³

(Contd. on page 6)

Safety data sheet according SS 586 : Part 3

Printing date 16.08.2023

Version number 1

Revision: 10.07.2023

Trade name: Concrete Primer

(Contd. of page 5)

- | | |
|---------------------------|-----------------|
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |

- | | |
|--|-----------------|
| · Solubility in / Miscibility with water: | Fully miscible. |
|--|-----------------|

- | | |
|--|-----------------|
| · Partition coefficient: n-octanol/water: | Not determined. |
|--|-----------------|

- | | |
|---------------------|-----------------|
| · Viscosity: | |
| · Dynamic: | Not determined. |
| · Kinematic: | Not determined. |

- | | |
|---------------------------|---------|
| · Solvent content: | |
| · VOC (EC) | 80.00 % |

- | | |
|----------------------------|--|
| · Other information | No further relevant information available. |
|----------------------------|--|

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
At elevated temperatures, explosive vapour/air mixtures may be formed.
- **Possibility of hazardous reactions**
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
Reacts violently with oxidising agents.
- **Conditions to avoid** Heat and static discharge.
- **Incompatible materials:** Strong acids and oxidising agents
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

- | | |
|--|--|
| · LD/LC50 values relevant for classification: | |
|--|--|

ATE (Acute Toxicity Estimates)

Oral	LD50	24,700 mg/kg (rabbit)
Inhalative	LC50/4 h	117 mg/l (rat)

67-64-1 Acetone

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet according SS 586 : Part 3

Printing date 16.08.2023

Version number 1

Revision: 10.07.2023

Trade name: Concrete Primer

(Contd. of page 6)

· **Additional toxicological information:**

INHALATION RISK: A harmful contamination of the air will be reached very quickly on evaporation of this substance at 20°C.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

67-64-1 Acetone

EC50 (96 h)	8,800 mg/l (Bacteria)
-------------	-----------------------

· **Persistence and degradability** No further relevant information available.

· **Behaviour in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

· **Uncleaned packaging:**

· **Recommendation:**

Container remains hazardous when empty. Continue to observe all precautions.

Disposal must be made according to official regulations.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

(Contd. on page 8)

**Safety data sheet
according SS 586 : Part 3**

Printing date 16.08.2023

Version number 1


Revision: 10.07.2023

Trade name: Concrete Primer

(Contd. of page 7)

· **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information

· UN-Number · ADR/RID/ADN, IMDG, IATA	UN1139
· UN proper shipping name · ADR/RID/ADN · IMDG, IATA	UN1139 COATING SOLUTION, special provision 640D COATING SOLUTION
· Transport hazard class(es) · ADR/RID/ADN, IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· Packing group · ADR/RID/ADN, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 9)

**Safety data sheet
according SS 586 : Part 3**

Printing date 16.08.2023

Version number 1

Revision: 10.07.2023

Trade name: Concrete Primer

(Contd. of page 8)

· **UN "Model Regulation":** UN 1139 COATING SOLUTION, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Poisons Act - Schedule 1**

None of the ingredients is listed.

· **Poisons Act - Schedule 2, Group II**

None of the ingredients is listed.

· **Health Products Act - First Schedule - Psychotropic Substances**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms** GHS02, GHS07

· **Signal word** Danger

· **Hazard statements**

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P5c

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t

· **National regulations:**

· **Information about limitation of use:**

Class	Share in %
NK	80.0

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)



Safety data sheet according SS 586 : Part 3

Printing date 16.08.2023

Version number 1

Revision: 10.07.2023

Trade name: Concrete Primer

(Contd. of page 9)

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Contact:**· Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3