



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

1 Identification

· **Product identifier**

· **Trade name:** Polished Concrete Sealer

· **Application of the substance / the mixture** Sealant

· **Uses advised against**

Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).

Any use involving aerosol formation or vapour release in excess of the assigned WEL where workers are exposed without suitable RPE.

Processes involving extreme heat use advised against.

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Coval Technologies

12811 Royal Drive, Suite 110

Stafford, TX 77477

email contact: sales@covaltechnologies.com

· **Information department:** Product safety department.

· **Emergency telephone number:**

CHEMTREC: 800-424-9300 (Domestic North America) OR 703-527-3887 (International, collect calls accepted).

2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms** GHS02, GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**

Isopropanol

n-butyl acetate

· **Hazard statements**

H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

Trade name: Polished Concrete Sealer

(Contd. of page 1)

- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P403+P235 Store in a well-ventilated place. Keep cool.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



HEALTH 2 Health = 2
FIRE 3 Fire = 3
REACTIVITY 0 Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

67-63-0	Isopropanol	20 - 60%
540-88-5	tert-butyl acetate	20 - 40%
123-86-4	n-butyl acetate	1 - 10%

· **Additional information:** *Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Check for and remove any contact lenses.

(Contd. on page 3)



Safety Data Sheet acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

Trade name: Polished Concrete Sealer

(Contd. of page 2)

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Wash mouth out with water

Do not induce vomiting; call for medical help immediately.

If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

· Information for doctor: Treat symptomatically and supportively.**· Most important symptoms and effects, both acute and delayed** Dizziness**· Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

* 5 Fire-fighting measures

· Extinguishing media**· Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

· For safety reasons unsuitable extinguishing agents: Water with full jet**· Special hazards arising from the substance or mixture**

In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Flammable. Vapors may travel to source of ignition and flash back.

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters**· Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

· Additional information

Cool endangered receptacles with water spray.

Absorb gas/vapours with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

* 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep ignition sources away - no smoking.

Vapours are heavier than air. They can spread along the ground and collect in confined spaces.

· Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Contaminated absorbent material may pose the same hazard as the spilt product.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

Trade name: Polished Concrete Sealer

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals**· PAC-1:**

67-63-0	Isopropanol	400 ppm
540-88-5	tert-butyl acetate	600 ppm
123-86-4	n-butyl acetate	5 ppm

· PAC-2:

67-63-0	Isopropanol	2000* ppm
540-88-5	tert-butyl acetate	1,700 ppm
123-86-4	n-butyl acetate	200 ppm

· PAC-3:

67-63-0	Isopropanol	12000** ppm
540-88-5	tert-butyl acetate	10,000 ppm
123-86-4	n-butyl acetate	3000* ppm

7 Handling and storage

· Handling:**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.**· Information about storage in one common storage facility:**

Do not store together with oxidizing and acidic materials.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Storage class: 3**· Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

Trade name: Polished Concrete Sealer

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-63-0 Isopropanol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

540-88-5 tert-butyl acetate

PEL	Long-term value: 950 mg/m ³ , 200 ppm
REL	Long-term value: 950 mg/m ³ , 200 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

· **Ingredients with biological limit values:**

67-63-0 Isopropanol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

Select PPE appropriate for the operations taking place taking into account the product properties.

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Contaminated clothes are a fire hazard. Rinse with plenty of water.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

· **Breathing equipment:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A for organic vapours

· **Protection of hands:**



Protective gloves.

Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

Trade name: Polished Concrete Sealer

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses with side-shields conforming to EN166.

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

· **Body protection:**



Flame retardant antistatic protective clothing.

Body protection must be chosen depending on product properties, activity and possible exposure.

· **Limitation and supervision of exposure into the environment**

Do not let product enter drains. Risk of explosion.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	82 °C (179.6 °F)

· **Flash point:** 25 °C (77 °F)

· **Flammability (solid, gaseous):** Flammable.

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

(Contd. on page 7)



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

Trade name: Polished Concrete Sealer

(Contd. of page 6)

· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	41 hPa (30.8 mm Hg)
· Density at 20 °C (68 °F):	0.8 g/cm ³ (6.676 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC content:	40–60 % 343.2 – 2,457.4 g/l / 2.86 – 20.51 lb/gal
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Heating will cause rise in pressure of container with risk of bursting.
At elevated temperatures, explosive vapour/air mixtures may be formed.
- **Possibility of hazardous reactions** Reacts violently with oxidizing agents.
- **Conditions to avoid** Heat and static discharge.
- **Incompatible materials:** Strong acids and oxidising agents
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:****67-63-0 Isopropanol**

Oral	LD50	> 2,000 mg/kg (rat)
------	------	---------------------

123-86-4 n-butyl acetate

Oral	LD50	> 2,000 mg/kg (rat)
Dermal	LD50	> 5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 21 mg/l (rat)

(Contd. on page 8)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

Trade name: Polished Concrete Sealer

(Contd. of page 7)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:**
No sensitizing effects known.
Based on available data, the classification criteria are not met.
- **Subacute to chronic toxicity:** Prolonged or repeated skin contact may irritate and cause dermatitis.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

67-63-0	Isopropanol	3
---------	-------------	---

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **Specific target organ toxicity - single exposure** May cause drowsiness or dizziness.
- **Specific target organ toxicity - repeated exposure**
Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

67-63-0 Isopropanol

EC50 (96 h) > 10,000 mg/l (Bacteria)

123-86-4 n-butyl acetate

EC50 (96 h) 44 mg/l (Bacteria)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** Contains components with the potential to bioaccumulate.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 9)



Safety Data Sheet acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

Trade name: Polished Concrete Sealer

· **Other adverse effects** No further relevant information available. (Contd. of page 8)

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Recommended Hierarchy of Controls:

- Minimize waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Contact waste processors for recycling information.

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning. Disposal must be made according to official regulations.

Container remains hazardous when empty. Continue to observe all precautions.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, ADR/RID/ADN, IMDG, IATA** UN1139

· **UN proper shipping name**

· DOT	Coating solution
· ADR/RID/ADN	UN1139 COATING SOLUTION
· IMDG, IATA	COATING SOLUTION

· **Transport hazard class(es)**

· **DOT**



· Class	3 Flammable liquids
· Label	3

(Contd. on page 10)

Safety Data Sheet acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

Trade name: Polished Concrete Sealer

(Contd. of page 9)

· ADR/RID/ADN, IMDG, IATA



· **Class** 3 Flammable liquids
 · **Label** 3

· **Packing group**
 · **DOT, ADR/RID/ADN, IMDG, IATA** III

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Flammable liquids
 · **Hazard identification number (Kemler code):** 30
 · **EMS Number:** F-E,S-E
 · **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· Transport/Additional information:

· **ADR/RID/ADN**
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· **IMDG**
 · **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 1139 COATING SOLUTION, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 No further relevant information available.
 · **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

67-63-0 Isopropanol

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

(Contd. on page 11)



Safety Data Sheet acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

Trade name: Polished Concrete Sealer

(Contd. of page 10)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

67-63-0 Isopropanol

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms GHS02, GHS07

· Signal word Warning

· Hazard-determining components of labeling:

Isopropanol
n-butyl acetate

· Hazard statements

H226 Flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P403+P235 Store in a well-ventilated place. Keep cool.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 12)



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/23/2024

Reviewed on 02/23/2024

Trade name: Polished Concrete Sealer

(Contd. of page 11)

- **Department issuing SDS:** Product safety department.
- **Contact:**
- **Date of preparation / last revision** 02/23/2024
- **Abbreviations and acronyms:**
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - BEI: Biological Exposure Limit
 - Flammable Liquids 3: Flammable liquids – Category 3
 - Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
 - Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
- *** Data compared to the previous version altered.**

-US-